

XP-D300M

Thermal Receipt Printer

Xprinter®

- Easy Maintenance: Support update firmware online easy drop-in paper loading
- User can search and manage Lan printer directly by software
- Fast printing speed up to 300mm/s
- Support placed vertically or horizontally



Restaurant



Shopping




Mart



Wall-hanging

XP-D300M

Thermal Receipt Printer



Printing		XP-D300M
Printing method	Direct thermal	
Paper width	79.5±0.5mm □80mm	
Print width	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm	
Column capacity	576 dots/line(adjustable by command)	
Printing speed	300 mm/s	
Interface	USB+Serial+Lan	
Line spacing	3.75mm (Adjustable by commands)	
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns	
Character size	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)	
Cutter		
Auto cutter	Partial	
Barcode Character		
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)	
Barcode types	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128	
2D Barcode	QR CODE / PDF417	
Input buffer	2048 Kbytes	
NVFlash	256 Kbytes	
Power		
Power adaptor	Input: AC 100-240V, 50 ~ 60Hz Output: DC 24V/2.5A	
Printer input	DC 24V/2.5A	
Cash drawer output	DC 24V/1A	
Physical characteristics		
Weight	1.44 Kg	
Dimensions	144.5×146×188.5mm (D×W×H)	
Environmental Requirements		
Work environment	Temperature (0 ~ 45℃) humidity(10 ~ 80%)	
Storage environment	Temperature(-10 ~ 60℃) humidity(10 ~ 80%)	
Reliability		
Cutter life	1.5 million cuts	
Printer head life	150 KM	
Software		
Emulation	ESC/POS	
Driver	Windows/JPOS/OPOS/Linux/Android/Mac	
Utility	Windows & Linux test Utility	
SDK	iOS/ Android/ Windows	



Scan QR code to checkout Xprinter website for more update information.
Phone: (+86 756) 3895 852
Http://www.xprintertech.com
Email: overseas@xprinter.net

